



# SAFETY DATA SHEET

## SHOOTERS CHOICE FP-10 LUBRICANT ELITE CLP

### SECTION 1: IDENTIFICATION

**Product Name:** FP-10 Lubricant Elite® CLP  
**Intended Use(s):** Product Code: SHF-FPL005, SHF-FPL036, SHF-FPL04, SHF-FPL128, SHF-75C-FP10 Firearms and weapon systems lubricant, cleaner and preservative

**Revision Date:** 03/03/22  
**Manufacturer:** OTIS TECHNOLOGY  
6987 Laura Street, Lyons Falls, NY 13368

**Information Telephone Number:** 1-800-674-7847  
**Emergency Contact:** Chemtrec: 800-424-9300  
International Chemtrec: 703-527-3887

### SECTION 2: HAZARDS IDENTIFICATION

**Classification**  
Acute toxicity, dermal - Category 5  
Skin corrosion / irritation - Category 3  
Serious eye damage / irritation - Category 2  
Skin sensitization - Category 1B

#### Label Elements

**Symbols:**



**Signal Word:** Warning

**Hazard Statement(s):** H313 May be harmful in contact with skin  
H316 Causes mild skin irritation  
H319 Causes serious eye irritation  
H317 May cause an allergic skin reaction

**Other Hazards (HNOC):** Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis.  
Repeated exposure at high levels may produce liver or kidney damage.

**Precautionary Statement(s):** P280 Wear eye protection; wear protective gloves.  
P261 Avoid breathing fume/mist/vapors/spray.  
P264 Wash thoroughly with soap and water after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P312 Get medical attention if exposed and you feel unwell.  
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P362 + P364 Take off contaminated clothing and wash it before reuse.  
P333 + P313 If skin irritation or rash occurs: Get medical attention.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical attention.

**Disposal:** P501 Dispose of product and/or container to a licensed waste disposal contractor in accordance with local, regional, national and international regulations.

#### HMIS III ratings (U.S.)

**Health:** 2 \*    **Flammability:** 1    **Physical hazards:** 0    **Personal protection:** None assigned - PPE codes should be determined by the employer, who is familiar with the actual conditions under which the material is used. See Section 8 for more information.

See Section 11 for complete health hazard information

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

Ingredient Name	CAS No	% by Weight*
Severely hydrotreated mineral oils consisting of one or more of the following: Distillates (petroleum), hydrotreated heavy naphthenic Distillates (petroleum), hydrotreated light naphthenic	64742-52-5 64742-53-6	70 - 83.9 %
Petroleum hydrocarbon oils	Confidential mixture*	20 - 29.9 %
Calcium sulfonate	61789-86-4	1 - 4.9 %
Butylated phenol	128-39-2	0 - 1.5 %

\* If Chemical Name/CAS No is "proprietary" or "confidential" and/or % by Weight is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

**SECTION 4: FIRST AID MEASURES****Inhalation:**

Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms occur.

**Skin contact:**

Wash with plenty of soap and water. Immediately remove contaminated clothing. Call a poison center or doctor if you feel unwell. If skin irritation or rash occurs: Get medical attention. Launder contaminated clothing before reuse. Discard leather articles saturated with material.

**Eye Contact:**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing for at least 15 minutes or until chemical is removed. If eye irritation persists: Get medical attention.

**Ingestion:**

Rinse mouth thoroughly with water. DO NOT induce vomiting. Call a poison center or doctor if you feel unwell. If vomiting occurs: get immediate medical attention.

**Most important symptoms / effects (acute and delayed):**

When heated or misted, inhalation of vapor or mists may cause irritation of mucous membranes and respiratory tract. High concentrations may cause headaches, nausea, dizziness, behavioral changes, stupor or drowsiness.

Skin contact may cause an allergic reaction. Repeated, frequent or prolonged skin contact may cause defatting of the skin which can lead to irritation and / or dermatitis. Symptoms may include redness, edema, drying and cracking of skin.

Eye contact may cause severe burning, stinging, tearing, redness or blurred vision.

Swallowing may cause irritation of gastrointestinal lining, nausea, and vomiting.

Repeated exposure to high levels may produce liver and kidney damage.

**Indication of immediate medical attention or special treatment, if necessary:**

If exposed or concerned: Get medical attention.

ADVICE TO PHYSICIANS: Treat symptomatically and supportively.

**Additional advice / information:**

None known.

See Section 11 for complete health hazard information.

**SECTION 5: FIRE-FIGHTING MEASURES****Suitable extinguishing media:**

Carbon dioxide, foam, dry chemical, water mist or fog. Water can be used to cool containers exposed to fire.

DO NOT use direct water jet or high-pressure stream.

**Hazardous combustion products:**

Smoke, irritating fumes and vapors, hydrogen chloride, aldehydes, oxides of carbon, nitrogen, phosphorus, sulfur and zinc and other toxic fumes. Hydrogen sulfide and alkyl mercaptans may also be released.

**Protection for firefighters:**

As in any fire, wear self-contained breathing apparatus operated in positive pressure mode and full protective gear.

Avoid water stream on molten burning material as it may scatter and spread the fire. Water or foam may cause frothing.

**Additional advice / information:**

Take no action involving personal risk or without suitable training. DO NOT release chemically contaminated water into drains, soil or surface water.

**NFPA hazard identification (U.S.):**

Health: 2      Flammability: 1      Instability: 0      Special hazards: ---

**SECTION 6: ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures:**

Evacuate personnel to safe area. Keep unnecessary personnel away. Stop leak if possible without risk. Eliminate all ignition sources if possible without risk. Avoid inhalation of vapors. Avoid contact with skin, eyes and clothing - do not touch or walk through spilled material. Spillages may be slippery. Wear protective clothing / equipment (see Section 8). Ventilate area if spilled in a confined space or other poorly ventilated area.

**Environmental precautions:**

Prevent from entering soil, ditches, sewers, waterways and groundwater. Do not flush into surface water, sanitary sewer or ground water system.

**Methods and materials for containment and clean-up:**

Contain spilled material. Absorb spill with a noncombustible material (i.e. vermiculite, sand or earth). Sweep, scoop, or vacuum the discharged material / spent absorbent. Seal absorbent material in a labeled container for later disposal. LARGE SPILLS: Stop material flow if possible without risk. Dike area far ahead of spill to prevent spreading. Pump liquid to salvage tank. Remaining liquid may be taken up on sand, clay, earth, or other absorbent material and shoveled into containers. Do NOT use combustible materials, such as saw dust. Seal and label containers for later disposal.

**Additional advice / information:**

NAERG No. 171

See Section 13 for disposal considerations.

**SECTION 7: HANDLING AND STORAGE****Precautions for safe handling:**

Avoid contact with eyes, skin, clothing and shoes. Avoid repeated or prolonged skin contact. Wear protective gloves and any other PPE deemed suitable (see Section 8). Avoid breathing fume, mist, vapors or spray. Use adequate ventilation and / or engineering controls (see Section 8). Keep away from ignition sources. When handling, DO NOT eat, drink or smoke. DO NOT ingest product. Wash face, hands and any exposed skin thoroughly with soap and water after handling. Contaminated work clothing should not be allowed out of the workplace. Launder contaminated clothing before reuse. Keep containers closed and upright when not in use. DO NOT reuse empty containers without cleaning or reconditioning. Empty container contains product residue which may exhibit hazards of the product. Avoid water contamination, incompatible conditions (see Section 10) and extreme temperatures to prevent product degradation.

**Conditions for safe storage, including incompatibilities:**

Keep in original container and tightly closed and sealed until ready for use. Store protected from sunlight in a cool, dry and well-ventilated place. Keep away from incompatible materials (see Section 10) and sources of ignition. Take precautions to avoid release to the environment. DO NOT store in unlabeled or mislabeled containers. Maximum storage temperature for product preservation: 40°C (104°F). Storage life: 2 years if stored according to advice given.

**Additional advice / information:**

Empty containers contain material residue. DO NOT cut, weld, braze, solder, drill, grind or expose containers to heat, flame, spark or other sources of ignition.

**SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION****Occupational exposure limits:**

Ingredient name	OSHA PEL	ACGIH TLV	Other
Severely refined mineral oils: Oil as mist, if generated	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	---
Petroleum hydrocarbon oils	Not established	Not established	---
Caesium sulfonate	Not established	Not established	---
Butylated phenol	Not established	Not established	---

(s) = skin      (c) = ceiling exposure

**Engineering controls:**

General ventilation is normally adequate. If use generates mist or vapor, local exhaust ventilation is recommended. Additional ventilation or exhaust may be required to maintain air concentrations below exposure limits. Thermal processing operations should be ventilated to prevent exposure to vapors.

## **Personal protective equipment**

### **Eye / face protection:**

Wear safety glasses. If potential for splash or mist exists, wear chemical splash goggles or face shield. Wear goggles, face shield or other full-face protection during thermal processing if contact with hot material is possible.

### **Skin / body protection:**

Use chemical-resistant gloves, i.e. nitrile or neoprene. Long-sleeve shirt recommended. Wear apron or coverall if there is a risk of exposure to splashes. Do not wear rings, watches or similar apparel that could entrap the material and cause a skin reaction. If handling HOT product, ensure gloves, boots and clothing are heat resistant and insulated.

### **Respiratory protection:**

Not usually required under normal conditions of use. If airborne concentrations are above exposure limits, use an approved respirator. Consult with an industrial hygienist to determine the appropriate respiratory protection for your specific use of this material.

### **Work and hygiene practices:**

Safety showers and eye wash stations should be provided close to work areas with splash hazards. Launder contaminated clothing and shoes before reuse. Follow general hygiene considerations recognized as common good work practices. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when handling product.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

<b>Appearance:</b>	Amber liquid.
<b>Odor:</b>	Mild petroleum, hint of cinnamon
<b>Odor threshold:</b>	Not determined
<b>pH:</b>	Not determined
<b>Melting / freezing point:</b>	Pour point: < - 45.6°C (- 50.0°F) ASTM D97
<b>Initial boiling point / range:</b>	> 232.2°C (450.0°F) ASTM D1120
<b>Flash point:</b>	144.5°C (292.1°F) ASTM D93
<b>Evaporation rate:</b>	Not determined
<b>Flammability / Explosive Limits:</b>	
<b>Upper:</b> Not determined.	<b>Lower:</b> Not determined.
<b>Vapor pressure:</b>	0.810 PSI ASTM D5191
<b>Vapor density:</b>	Not determined
<b>Specific gravity:</b>	0.9452 ASTM D1298
<b>Relative density:</b>	0.9447 g/cm <sup>3</sup> ASTM D1298
<b>Solubility(ies):</b>	Insoluble (water).
<b>Partition coefficient: n-Octanol/water</b>	Not determined
<b>Auto-ignition temperature:</b>	243°C (469.4°F)
<b>Decomposition temperature:</b>	Not determined
<b>Viscosity:</b>	25.05 cSt @ 40°C / 3.969 cSt @ 100°C ASTM D445

*The above properties are typical values and do NOT constitute a product specification.*

## **SECTION 10: STABILITY AND REACTIVITY**

### **Stability:**

Stable under normal handling and storage conditions (see Section 7).

### **Possibility of hazardous reactions:**

None known under normal conditions of use.

As with all petroleum chemicals, product tends to soften or swell most natural rubbers. Can react with iron, zinc and aluminum at high temperatures leading to product decomposition.

### **Conditions to avoid:**

Direct sunlight, high temperatures, and sources of ignition. Strong oxidizing conditions. Contact with strong caustic agents.

### **Incompatible materials:**

Strong oxidizing agents. Reducing agents. Acids.

**Hazardous decomposition products:**

Smoke, irritating vapors, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion. Hydrogen sulfide and alkyl mercaptans and sulfides may also be released. Under combustion conditions, oxides of phosphorus, sulfur, calcium and zinc may form. Prolonged heating at temperatures in excess of 70°C (158°F), OR heating above 200°C (392°F) for short periods of time, will result in product decomposition and possible liberation of hydrogen chloride.

**SECTION 11: TOXICOLOGICAL INFORMATION****Information on toxicological effects**

Likely routes of exposure: Skin contact, eye contact, inhalation.

**Acute exposure**

Oral toxicity: No data on product. LD50 rats > 5000 mg/kg based on component data. Swallowing may cause nausea, vomiting and irritation of gastrointestinal tract.

Dermal toxicity: No data on product. May be harmful in contact with skin. LD50 rabbits > 2500 mg/kg based on component data.

Inhalation toxicity: No data available to indicate product or components may be a toxic inhalation hazard. When heated or misted, vapor or mists may irritate mucous membranes and respiratory tract. High concentrations may cause headaches, dizziness, nausea, behavioral changes, weakness, drowsiness and stupor. Based on component data.

Skin corrosion / irritation: Causes mild skin irritation. Based on component data.

Eye damage / irritation: Causes serious eye irritation. Based on component data. Symptoms may include burning, stinging, tearing, redness, and blurred vision.

Sensitization – skin / respiratory: May cause skin sensitization based on component data.

**Chronic exposure**

Germ cell mutagenicity: No data available to indicate product or its components present at 0.1% or greater are mutagenic.

Carcinogenicity: Severely hydrotreated naphthenic petroleum oils have not been found to be carcinogenic or potential carcinogens. The oils in this product contain < 3.0% DMSO extractable compounds by IP 346.

Reproductive toxicity: No data available to indicate product or its components present at 0.1% or greater cause reproductive toxicity.

**Specific target organ toxicity (STOT)**

Single exposure: None known.

Repeated / prolonged exposure: Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying and cracking of skin. Repeated exposure to high levels may produce liver or kidney damage. In a 28-day oral toxicity study in rats, 2,6-Di-tert-butylphenol showed an increase in liver weight with corresponding histopathology at 600 mg/kg-bw/day; a NOAEL of 100 mg/kg-bw/day was established for systemic toxicity.

**Aspiration hazard**

Not classed.

**SECTION 12: ECOLOGICAL INFORMATION****Ecotoxicity:**

This product is not classified as environmentally hazardous under normal conditions of use. However, this does not exclude the possibility that large or frequent releases to water or sediment can have a harmful or damaging effect on the environment. Based on component data.

**Persistence / degradability:**

No data on product. Not readily biodegradable based on component data.

**Bioaccumulative potential:**

No data on product. More than 70% of components are expected to have a high potential to bioaccumulate.

**Mobility:**

No data on product. Essentially insoluble to water based on component data.

**Ozone depletion:**

No known ingredients present at 0.1% or greater are identified as ozone-depleting substances.

**Other adverse effects:**

None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

### Disposal:

Avoid release to the environment. DO NOT dispose of to any sewer, ground or body of water. Dispose to a licensed waste disposal contractor in accordance with local, regional, national or international regulations.

### Empty containers:

Empty containers may contain harmful residue or vapors. Labels should not be removed from containers until they have been cleaned. Dispose of or recycle packaging in accordance with local, regional, national or international regulations.

### Additional advice / information:

It is the responsibility of the user to determine, at the time of disposal, whether product meets the RCRA criteria for hazardous waste.

## SECTION 14: TRANSPORT INFORMATION

### U.S. Dept. of Transportation (DOT):

	Non-Bulk	Bulk *
UN Number	Not regulated.	Not regulated.
Proper Shipping Name	Lubricant oil	Lubricant oil
Hazard Class	Not applicable.	Not applicable.
Packing Group	Not applicable.	Not applicable.
Special provisions	Not applicable.	Not applicable.
Packaging exceptions	Not applicable.	Not applicable.
NAERG number	171	171
Placard advisory	Not applicable.	Not applicable.
Label(s) required	Not applicable.	Not applicable.
Quantity Limitations:		
Passenger aircraft/rail	Not applicable.	Not applicable.
Cargo aircraft only	Not applicable.	Not applicable.

### UN Model Regulations (annexes to the Recommendations on the Transport of Dangerous Goods):

Not determined.

### IMDG Code:

Product does not meet the criteria for marine pollutant classification. See U.S. DOT.

### IBC Code / Annex II of MARPOL 73/78:

Not determined.

**Additional advice / information:** \* Review classification requirements before shipping material at elevated temperatures.

## SECTION 15: REGULATORY INFORMATION

### U.S. Federal Regulations:

TSCA: All components are on the inventory or exempt from listing.

Other TSCA: Section 8D (2,6-Di-tert-butylphenol).

SARA Title III:

Sections 311/312 Hazard Classes:

Acute health hazard:	Yes
Chronic health hazard:	Yes
Fire hazard:	Yes
Reactive hazard:	No
Release of pressure hazard:	No

Section 313 Form R reporting:

This product does not contain greater than 1.0% (greater than 0.1% for carcinogenic substance) of any chemical substances listed under SARA Section 313.

Section 302 Extremely Hazardous Substances (EHS) / CERCLA Hazardous Substances:

SARA EHS: This product does not contain greater than 1.0% of any chemical substances on the list of SARA Extremely Hazardous Substances.

CERCLA: None known.

**U.S. State Regulations:**

- California: Product does not intentionally contain any Proposition 65 chemicals. Additionally, we do not routinely analyze products for impurities, which may be such chemicals.
- New Jersey RTK: CASRN 64742-52-5 Hydrotreated heavy naphthenic distillates (petroleum), listed. CASRN 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic, listed.
- Pennsylvania RTK: CASRN 64742-52-5 Hydrotreated heavy naphthenic distillates (petroleum), listed. CASRN 64742-53-6 Distillates (petroleum), hydrotreated light naphthenic, listed.

**International Inventories:**

Components of this product are compliant with, or listed on, one or more of the following: Australia, Canada, China, Europe, Japan, Korea, New Zealand, Philippines, Switzerland, Taiwan.

**Other regulatory information:** None.

**SECTION 16: OTHER INFORMATION****SDS History**

Issue date: 8 September 2005  
Revision date: 02/01/18  
Revision number: 06  
Revision indicator: This SDS has been revised as follows:  
Update for company name change  
Prepared by: Technical Dept.

**Acronym Legend:**

ACGIH American Conference of Governmental Industrial Hygienists  
BCF Bioconcentration Factor  
CAS Chemical Abstracts Service  
CERCLA Comprehensive Environmental Response, Compensation and Liability Act (Superfund)  
EPCRA Emergency Planning and Community Right-to-Know  
GHS Globally Harmonized System of Classification and Labelling of Chemicals  
HMIS Hazardous Material Information System  
IARC International Agency for Research on Cancer  
IBC Intermediate Bulk Container  
IMDG International Maritime Dangerous Goods Code  
LC<sub>50</sub> Lethal Concentration  
LD<sub>50</sub> Lethal Dose  
LOAEL Lowest Observed Adverse Effect Level  
NFPA National Fire Protection Association  
NIOSH National Institute for Occupational Safety & Health  
NOAEL No Observed Adverse Effect Level  
NTP National Toxicology Program  
OSHA Occupational Health and Safety Administration  
PEL Permissible Exposure Limit  
RQ Reportable Quantity  
SARA U.S. EPA Superfund Amendments and Reauthorization Act  
STEL Short-Term Exposure Limit  
TLV Threshold Limit Value  
TPQ Threshold Planning Quantity  
TWA Time-Weighted Average  
VOC Volatile Organic Compound

The information contained in this document applies to this specific material as supplied, and is accurate to the best of our knowledge. However, the conditions of handling, storage, or misuse, are beyond our control, therefore, Shooters Choice LLC makes NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. This data is for information purposes only. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for his/her own particular use.

- END SAFETY DATA SHEET -