

Safety Data Sheetaccording to Regulation (EU) 2015/830
Date of issue: 1/22/2020 Version: 1.0**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**Product form : Mixture
Product name : Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1. Relevant identified uses**Industrial/Professional use spec : Industrial
For professional use only
Use of the substance/mixture : Coatings and paints, thinners, paint removers**1.2.2. Uses advised against**

Restrictions on use : No additional information available

1.3. Details of the supplier of the safety data sheet

LA-CO Industries Europe S.A.S.

Parc Industriel de la Plaine de

l'Ain - Allée des Combes.

01150.BLYES.France.

Phone: +33 (0)4 74 46 23 23

Fax: +33 (0)4 74 46 23 29

E-mail: info@eu.laco.com

Web: http://www.markal.com

1.4. Emergency telephone numberEmergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887;
全国应急中心 0532 8388 9090

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
AUSTRIA	Vergiftungsinformationszentrale (Poisons Information Centre)	Allgemeines Krankenhaus Waehringer Geurtel 18-20 1090 Wien	+43 1 406 43 43
BELARUS	The Belarus Republican Poisons Centre	Kizhevatova str. 58 Minsk 220115	+375 (0)17 201 9158
BELGIUM	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 B -1120 Bruxelles/Brussel	+32 70 245 245
BULGARIA	Национален токсикологичен информационен център National Clinical Toxicology Centre, Emergency Medical Institute "Pirogov"	21 Tottleben Boulevard 1606 SOFIA	+359 2 9154 409
CROATIA	Poisons Control Centre Institute of Medical Research & Occupational Health	Ksaverska Cesta 2 P.O. Box 291 HR-10000 Zagreb	+385 1 234 8342
CZECH REPUBLIC	Toxikologické informační středisko Clinic For Occupational Medicine, 1st Medical Faculty, Charles University	Na Bojišti 1 120 00 Praha 2	+42 2 2491 9293 +42 2 2491 5402
DENMARK	Giftlinjen Bispebjerg Hospital	Bispebjerg Bakke 23, 60, 1 DK-2400 København NV	+45 82 12 12 12 +45 35 31 55 55
ESTONIA	Mürgistusteabekeskus	Gonsiori 29 15027 Tallinn	+372 626 93 90
FINLAND	Myrkytystietokeskus	P.O.B 340 (Haartmaninkatu 4) HUS SF - 00029 Helsinki	+358 9 471 977
FRANCE	ORFILA		+33 1 45 42 59 59
GERMANY	Berliner Betrieb für Zentrale Gesundheitliche Aufgaben	Oranienburger Strasse 285 13437 Berlin	+49 30 19240
GERMANY	Informations und Beratungszentrum für Vergiftungsfälle	Kirberger Straße, Gebäude 9 D-66421 Homburg/Saar	+49 6841 19240
GERMANY	Beratungstelle bei Vergiftungen, Klinische Toxikologie und Beratungsstelle bei Vergiftungen	Langenbeckstrasse 1 55131 Mainz	+49 6131 19240
GREECE	Poisons Information Centre	11527 Athens	+30 10 779 3777
HUNGARY	Országos Kémiai Biztonsági Intézet (National Institute of Chemical Safety) Egészségügyi Toxikológiai Tájékoztató Szolgálat (Health Toxicological Information Service)	1437 Budapest PO Box 839 1097 Budapest, Nagyvárad tér 2	+36 80 20 11 99

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

EU Member State	Officieel adviesorgaan	Adres	Noodnummer
ICELAND	Eitrunarmiðstöðin	Eitrunarmiðstöðin 108 Reykjavik	+354 543 22 22
IRELAND	National Poisons Information Centre	Beaumont Hospital PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2166
LATVIA	Valsts Toksikoloģijas centra Saindēšanās un zāļu informācijas centrs	2 Hipocrate Street LV 1038 Riga	+371 67 04 24 73
LITHUANIA	Apsinuodijimų kontrolės ir informacijos biuras	Siltnamiu 29 2043 Vilnius	+370 5 236 20 52/+370 687 53 378
MALTA	Medicines & Poisons Info Office	Mater Dei Hospital, Msida MSD 2090 Malta	25450000
NETHERLANDS	Nationaal Vergiftigingen Informatie Centrum National Institute for Public Health and the Environment, NB this service is only available to health professionals	Huispostnummer B.00.118, PO Box 85500 3508 GA Utrecht	+31 30 274 88 88
PORTUGAL	Centro de Informação Antivenenos Instituto Nacional de Emergência Médica (INEM)	Rua Almirante Barroso, 36 1000-013 Lisboa	808 250 143 (for use only in Portugal), +351 21 330 3284
ROMANIA	Biroul pentru Regulamentul Sanitar International si Informare Toxicologica	Str. Dr. Leonte Anastasievici Nr.1-3, Sector 5 50463 Bucuresti	+40 21 318 36 06
SLOVAKIA	Národné toxikologické informačné centrum University Hospital Bratislava	Limbová 5 833 05 Bratislava	+421 2 54 77 4 166
SPAIN	Servicio de Información Toxicológica Instituto Nacional de Toxicología, Departamento de Madrid	Calle Luis Cabrera 9 E-28002 Madrid	+34 91 562 04 20
SWEDEN	Giftinformationscentralen Swedish Poisons Information Centre, Karolinska Hospital	Box 60 500 SE-171 76 Stockholm	+46 8 33 12 31 (International) 112 (National)
SWITZERLAND	Centre Suisse d'Information Toxicologique	Freiestrasse 16 Postfach CH-8028 Zurich	+41 44 251 51 51 (International) 145 (National)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (inhalation:dust,mist) Category 4	H332
Serious eye damage/eye irritation, Category 2	H319
Germ cell mutagenicity, Category 2	H341
Carcinogenicity, Category 1B	H350
Reproductive toxicity, Category 2	H361
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412
Full text of H statements : see section 16	

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS08

Signal word (CLP)

: Danger

Hazardous ingredients

: Phenolphthalein

Hazard statements (CLP)

: H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H341 - Suspected of causing genetic defects.
H350 - May cause cancer.
H361 - Suspected of damaging fertility or the unborn child.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313 - IF exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CENTRE/doctor/... if you feel unwell.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P405 - Store locked up.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

PBT: not yet assessed

vPvB: not yet assessed

SECTION 3: Composition/information on ingredients

3.1. Substances

Not regulated.

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
trans-dichloroethylene (Note C)	(CAS-No.) 156-60-5 (EC-No.) 205-860-2 (EC Index-No.) 602-026-00-3	30 - 50	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Aquatic Chronic 3, H412
Phenolphthalein substance listed as REACH Candidate	(CAS-No.) 77-09-8 (EC-No.) 201-004-7 (EC Index-No.) 604-076-00-1	1 - 30	Muta. 2, H341 Carc. 1B, H350 Repr. 2, H361f
1,1,1 Tris Ethane	(CAS-No.) 27955-94-8 (EC-No.) 405-800-7 (EC Index-No.) 604-048-00-9	0 - <25	Aquatic Chronic 2, H411
Isopropanol	(CAS-No.) 67-63-0 (EC-No.) 200-661-7 (EC Index-No.) 603-117-00-0	5 - <20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Methyl nonafluoroisobutyl ether	(CAS-No.) 163702-08-7 (EC-No.) 605-340-9	1 - 7	Acute Tox. 4 (Inhalation), H332
Methyl nonafluorobutyl ether	(CAS-No.) 163702-07-6 (EC-No.) 605-339-3	1 - 7	Acute Tox. 4 (Inhalation), H332
Xylenes (Note C)	(CAS-No.) 1330-20-7 (EC-No.) 215-535-7 (EC Index-No.) 601-022-00-9 (REACH-no) 01-2119488216-32	0.1 - 0.5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315
29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper	(CAS-No.) 147-14-8 (EC-No.) 205-685-1	0.1 - 0.5	Not classified
ethylbenzene	(CAS-No.) 100-41-4 (EC-No.) 202-849-4 (EC Index-No.) 601-023-00-4 (REACH-no) 01-2119489370-35	<0.1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:dust,mist), H332 STOT RE 2, H373 Asp. Tox. 1, H304
Carbon black	(CAS-No.) 1333-86-4 (EC-No.) 215-609-9	<0.1	Carc. 2, H351
Toluene	(CAS-No.) 108-88-3 (EC-No.) 203-625-9 (EC Index-No.) 601-021-00-3	<0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Repr. 2, H361d STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304 Aquatic Chronic 3, H412

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Benzene (Note E (obsolete))	(CAS-No.) 71-43-2 (EC-No.) 200-753-7 (EC Index-No.) 601-020-00-8	<0.1	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350 STOT RE 1, H372 Asp. Tox. 1, H304
2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether	(CAS-No.) 112-34-5 (EC-No.) 203-961-6 (EC Index-No.) 603-096-00-8	<0.1	Eye Irrit. 2, H319
Specific concentration limits:			
Name	Product identifier	Specific concentration limits	
Phenolphthalein	(CAS-No.) 77-09-8 (EC-No.) 201-004-7 (EC Index-No.) 604-076-00-1	(1 ≤ C ≤ 100) Carc. 1B, H350	

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note E : Substances with specific effects on human health (see Chapter 4 of Annex VI to Directive 67/548/EEC) that are classified as carcinogenic, mutagenic and/or toxic for reproduction in categories 1 or 2 are ascribed Note E if they are also classified as very toxic (T+), toxic (T) or harmful (Xn). For these substances, the risk phrases R20, R21, R22, R23, R24, R25, R26, R27, R28, R39, R68 (harmful), R48 and R65 and all combinations of these risk phrases shall be preceded by the word 'Also'. (obsolete)

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: Suspected of damaging fertility or the unborn child. Suspected of causing genetic defects. May cause cancer.
Symptoms/effects after inhalation	: Harmful if inhaled. Dizziness. Vapours are heavier than air and can cause suffocation by reducing oxygen available for breathing.
Symptoms/effects after eye contact	: Causes serious eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Carbon dioxide. dry extinguishing powder. Large fires: Water spray. alcohol resistant foam.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not flammable. Flammable vapours may accumulate in the container. Burning produces irritating, toxic and noxious fumes.
Explosion hazard	: Heat may build pressure, rupturing closed containers.

5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing. EN469.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Avoid contact with skin, eyes and clothing. Do not breathe vapour. Do not breathe aerosol.
------------------	--

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

6.1.1. For non-emergency personnel

Protective equipment : Refer to section 8.2.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Refer to section 8.2.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. Use only outdoors or in a well-ventilated area. Avoid contact with skin, eyes and clothing. Do not breathe aerosol. Do not breathe vapours.
Hygiene measures : Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety procedures. Use drum pumps, do not pour.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container. Keep container tight closed.
Incompatible products : Alkali metals. Alkaline earth metals. Powdered metallic salts. Strong bases.
Incompatible materials : Sources of ignition. Direct sunlight.
Storage temperature : < 37.8 °C
Heat and ignition sources : Keep away from heat, sparks and flame.

7.3. Specific end use(s)

Coatings and paints, thinners, paint removers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)

Germany	TRGS 910 Acceptable concentration notes	
Latvia	Local name	Vara ftalocianīns
Latvia	OEL TWA (mg/m³)	5 mg/m³
Latvia	Regulatory reference	Ministru kabineta 2007.gada 15.maija noteikumiem Nr.325 (Grozījumi Ministru kabineta 2011.gada 1.februārī noteikumiem Nr.92)

ethylbenzene (100-41-4)

EU	Local name	Ethylbenzene
EU	IOELV TWA (mg/m³)	442 mg/m³
EU	IOELV TWA (ppm)	100 ppm
EU	IOELV STEL (mg/m³)	884 mg/m³
EU	IOELV STEL (ppm)	200 ppm
EU	Notes	Skin
Austria	MAK (mg/m³)	440 mg/m³ (H)
Austria	MAK (ppm)	100 ppm (H)
Austria	MAK Short time value (mg/m³)	880 mg/m³ max. 8x5 min./Schicht (gemessen als Momentanwert), (H)
Austria	MAK Short time value (ppm)	200 ppm max. 8x5 min./Schicht (gemessen als Momentanwert), (H)
Belgium	Limit value (mg/m³)	442 mg/m³

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

ethylbenzene (100-41-4)		
Belgium	Limit value (ppm)	100 ppm
Belgium	Short time value (mg/m³)	551 mg/m³
Belgium	Short time value (ppm)	125 ppm
Belgium	Remark (BE)	D
Czech Republic	Local name	Ethylbenzen
Czech Republic	Expoziční limity (PEL) (mg/m³)	200 mg/m³
Czech Republic	Expoziční limity (PEL) (ppm)	46 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m³)	500 mg/m³
Czech Republic	Expoziční limity (NPK-P) (ppm)	115 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Ethylbenzen
Denmark	Grænseværdie (langvarig) (mg/m³)	217 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Denmark	Grænseværdie (kortvarig) (mg/m³)	434 mg/m³
Denmark	Grænseværdie (kortvarig) (ppm)	100 ppm
Denmark	Anmærkninger (DK)	K
Finland	Local name	Etylibentseeni
Finland	HTP-arvo (8h) (mg/m³)	220 mg/m³ iho
Finland	HTP-arvo (8h) (ppm)	50 ppm iho 5.2 ppm (Virtsan mantelihappo, Työvuoron päätyttyä työviikon tai altistumisjakson loputtua)
Finland	HTP-arvo (15 min)	880 mg/m³ iho
Finland	HTP-arvo (15 min) (ppm)	200 ppm iho
France	Local name	Ethylbenzène
France	VME (mg/m³)	88.4 mg/m³
France	VME (ppm)	20 ppm
France	VLE (mg/m³)	442 mg/m³
France	VLE (ppm)	100 ppm
France	Note (FR)	Peau
Germany	TRGS 900 Local name	Ethylbenzol
Germany	Occupational exposure limit value (mg/m³)	440 mg/m³
Germany	Occupational exposure limit value (ppm)	100 ppm
Germany	TRGS 903 Biological limit value	1 mg/l Ethylbenzol (Blut; Expositionsende bzw. Schichtende) 800 mg/l Mandelsäure + Phenylglyoxylsäure (Urin; Expositionsende bzw. Schichtende)
Germany	TRGS 910 Acceptable concentration notes	
Hungary	Local name	ETILBENZOL
Hungary	AK-érték	442 mg/m³
Hungary	CK-érték	884 mg/m³
Ireland	OEL (8 hours ref) (mg/m³)	442 mg/m³
Ireland	OEL (8 hours ref) (ppm)	100 ppm
Ireland	OEL (15 min ref) (mg/m³)	884 mg/m³
Ireland	OEL (15 min ref) (ppm)	200 ppm
Italy	Local name	Etilbenzene
Italy	OEL TWA (mg/m³)	442 mg/m³

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

ethylbenzene (100-41-4)		
Italy	OEL TWA (ppm)	100 ppm
Italy	OEL STEL (mg/m³)	884 mg/m³
Italy	OEL STEL (ppm)	200 ppm
Latvia	Local name	Etilbenzols
Latvia	OEL TWA (mg/m³)	442 mg/m³
Latvia	OEL TWA (ppm)	100 ppm
Latvia	OEL STEL (mg/m³)	884 mg/m³
Latvia	OEL STEL (ppm)	200 ppm
Lithuania	IPRV (mg/m³)	442 mg/m³
Lithuania	IPRV (ppm)	100 ppm
Lithuania	TPRV (mg/m³)	884 mg/m³
Lithuania	TPRV (ppm)	200 ppm
Lithuania	Remark (LT)	O
Netherlands	Local name	Ethylbenzeen
Netherlands	Grenswaarde TGG 8H (mg/m³)	215 mg/m³
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	430 mg/m³
Poland	Local name	Etylobenzen
Poland	NDS (mg/m³)	200 mg/m³
Poland	NDSch (mg/m³)	400 mg/m³
Portugal	Local name	Etilbenzeno
Portugal	OEL TWA (ppm)	20 ppm
Slovakia	Local name	Etylbenzén
Slovakia	NPHV (priemerná) (mg/m³)	442 mg/m³ (K)
Slovakia	NPHV (priemerná) (ppm)	100 ppm (K) 12 ppm (2 - a 4 -Etylfenol) 1600 ppm (Kyselina mandlová a kyselina fenylglyoxylová)
Slovakia	OEL STEL (mg/m³)	884 mg/m³
Slovakia	OEL STEL (ppm)	200 ppm
Slovenia	Local name	etilbenzen
Slovenia	OEL TWA (mg/m³)	442 mg/m³
Slovenia	OEL TWA (ppm)	100 ppm
Slovenia	OEL STEL (mg/m³)	884 mg/m³
Slovenia	OEL STEL (ppm)	200 ppm
Spain	Local name	Etilbenceno
Spain	VLA-ED (mg/m³)	441 mg/m³ vía dérmica, VLB, VLI
Spain	VLA-ED (ppm)	100 ppm vía dérmica, VLB, VLI 700 ppm I, S "(Suma del ácido mandélico y el ácido fenilglicólico en orina; Final de la semana laboral 1)"
Spain	VLA-EC (mg/m³)	884 mg/m³ vía dérmica, VLB, VLI
Spain	VLA-EC (ppm)	200 ppm vía dérmica, VLB, VLI
Sweden	Local name	Etylbensen
Sweden	nivågränsvärde (NVG) (mg/m³)	200 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	450 mg/m³
Sweden	kortidsvärde (KTV) (ppm)	100 ppm

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

ethylbenzene (100-41-4)		
United Kingdom	WEL TWA (mg/m³)	441 mg/m³
United Kingdom	WEL TWA (ppm)	100 ppm
United Kingdom	WEL STEL (mg/m³)	552 mg/m³
United Kingdom	WEL STEL (ppm)	125 ppm
United Kingdom	Remark (WEL)	(Sk)
Norway	Local name	Etylbenzen
Norway	Grænseverdier (AN) (mg/m³)	20 mg/m³
Norway	Grænseverdier (AN) (ppm)	5 ppm
Norway	Merknader (NO)	HK
Switzerland	VME (mg/m³)	435 mg/m³
Switzerland	MAK (ppm)	100 ppm 1.5 ppm Etilbenzene (sangue; fine dell'esposizione / del turno) 2 ppm Acido mandelico + acido fenilgliosilico (urina; fine dell'esposizione / del turno)
Switzerland	KZGW (mg/m³)	435 mg/m³
Switzerland	KZGW (ppm)	100 ppm

Toluene (108-88-3)		
EU	Local name	Toluene
EU	IOELV TWA (mg/m³)	192 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	384 mg/m³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	skin
Austria	MAK (mg/m³)	190 mg/m³ (H,d)
Austria	MAK (ppm)	50 ppm (H,d)
Austria	MAK Short time value (mg/m³)	380 mg/m³ max. 4x15 min./Schicht, (H,d)
Austria	MAK Short time value (ppm)	100 ppm max. 4x15 min./Schicht, (H,d)
Belgium	Limit value (mg/m³)	77 mg/m³
Belgium	Limit value (ppm)	20 ppm
Belgium	Short time value (mg/m³)	384 mg/m³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
Czech Republic	Local name	Toluen
Czech Republic	Expoziční limity (PEL) (mg/m³)	200 mg/m³
Czech Republic	Expoziční limity (PEL) (ppm)	53 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m³)	500 mg/m³
Czech Republic	Expoziční limity (NPK-P) (ppm)	130 ppm
Czech Republic	Remark (CZ)	D
Denmark	Local name	Toluen (Methylbenzen; Phenylmethan)
Denmark	Grænseværdie (langvarig) (mg/m³)	94 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Denmark	Grænseværdie (kortvarig) (mg/m³)	188 mg/m³
Denmark	Grænseværdie (kortvarig) (ppm)	50 ppm
Denmark	Anmærkninger (DK)	E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden)

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Toluene (108-88-3)		
Finland	Local name	Toluene
Finland	HTP-arvo (8h) (mg/m³)	81 mg/m³
Finland	HTP-arvo (8h) (ppm)	25 ppm
Finland	HTP-arvo (15 min)	380 mg/m³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Finland	Huomautus (FI)	iho, melu
France	Local name	Toluène
France	VME (mg/m³)	76.8 mg/m³
France	VME (ppm)	20 ppm
France	VLE (mg/m³)	384 mg/m³
France	VLE (ppm)	100 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; substance classée toxique pour la reproduction de catégorie 2; risque de pénétration percutanée
Germany	TRGS 900 Local name	Toluol
Germany	Occupational exposure limit value (mg/m³)	190 mg/m³
Germany	Occupational exposure limit value (ppm)	50 ppm
Germany	TRGS 900 Remark	DFG,EU,H,Y
Germany	TRGS 903 Biological limit value	3 mg/l o-Kresol (Urin; bei Langzeitexposition/Expositionsende bzw. Schichtende) 1 mg/l Toluol (Blut; Expositionsende bzw. Schichtende)
Germany	TRGS 910 Acceptable concentration notes	
Hungary	Local name	TOLUOL
Hungary	AK-érték	190 mg/m³
Hungary	CK-érték	380 mg/m³
Hungary	Megjegyzések (HU)	b, i; II.2.
Ireland	OEL (8 hours ref) (mg/m³)	192 mg/m³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m³)	384 mg/m³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Italy	Local name	Toluene
Italy	OEL TWA (mg/m³)	192 mg/m³
Italy	OEL TWA (ppm)	50 ppm
Latvia	Local name	Toluols (metilbenzols)
Latvia	OEL TWA (mg/m³)	50 mg/m³
Latvia	OEL TWA (ppm)	14 ppm
Latvia	OEL STEL (mg/m³)	150 mg/m³
Latvia	OEL STEL (ppm)	40 ppm
Lithuania	IPRV (mg/m³)	192 mg/m³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m³)	384 mg/m³
Lithuania	TPRV (ppm)	100 ppm
Lithuania	Remark (LT)	O
Netherlands	Local name	Toluene
Netherlands	Grenswaarde TGG 8H (mg/m³)	150 mg/m³
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	384 mg/m³

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Toluene (108-88-3)		
Poland	Local name	Toluen
Poland	NDS (mg/m³)	100 mg/m³
Poland	NDSch (mg/m³)	200 mg/m³
Portugal	Local name	Tolueno
Portugal	OEL TWA (ppm)	20 ppm
Slovakia	Local name	Toluén
Slovakia	NPHV (priemerná) (mg/m³)	192 mg/m³ (K)
Slovakia	NPHV (priemerná) (ppm)	50 ppm (K) 600 ppm (Toluén) 1.5 ppm (O-krezol) 2401 ppm (Kyselina hippurová)
Slovakia	OEL STEL (mg/m³)	384 mg/m³
Slovakia	OEL STEL (ppm)	100 ppm
Slovenia	Local name	toluen
Slovenia	OEL TWA (mg/m³)	192 mg/m³
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	OEL STEL (mg/m³)	384 mg/m³
Slovenia	OEL STEL (ppm)	100 ppm
Spain	Local name	Tolueno
Spain	VLA-ED (mg/m³)	192 mg/m³
Spain	VLA-ED (ppm)	50 ppm
Spain	VLA-EC (mg/m³)	384 mg/m³
Spain	VLA-EC (ppm)	100 ppm
Spain	Notes	Vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento), VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Sweden	Local name	Toluen
Sweden	nivågränsvärde (NVG) (mg/m³)	192 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	384 mg/m³

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Toluene (108-88-3)		
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Sweden	Anmärkning (SE)	B (Ämnet kan orsaka hörselskada Exponering för ämnet nära det befintliga yrkeshygieniska gränsvärdet och vid samtidig exponering för buller nära insatsvärdet 80 dB kan orsaka hörselskada); H (Ämnet kan lätt upptas genom huden Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
United Kingdom	WEL TWA (mg/m³)	191 mg/m³
United Kingdom	WEL TWA (ppm)	50 ppm
United Kingdom	WEL STEL (mg/m³)	384 mg/m³
United Kingdom	WEL STEL (ppm)	100 ppm
United Kingdom	Remark (WEL)	(Sk)
Norway	Local name	Toluen
Norway	Grenseverdier (AN) (mg/m³)	94 mg/m³
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Merknader (NO)	H (Kjemikalier som kan tas opp gjennom huden); E (EU har en veiledende grenseverdi for stoffet)
Switzerland	VME (mg/m³)	190 mg/m³
Switzerland	MAK (ppm)	50 ppm 0.6 ppm toluolo (sangue; fine dell'esposizione / del turno) 0.5 ppm o-cresolo (urina; in caso di esposizione per molto tempo/fine dell'esposizione / del turno)
Switzerland	KZGW (mg/m³)	760 mg/m³ max. 4x15 min./turno
Switzerland	KZGW (ppm)	200 ppm max. 4x15 min./turno

Xylenes (1330-20-7)		
EU	Local name	Xylene, mixed isomers, pure
EU	IOELV TWA (mg/m³)	221 mg/m³
EU	IOELV TWA (ppm)	50 ppm
EU	IOELV STEL (mg/m³)	442 mg/m³
EU	IOELV STEL (ppm)	100 ppm
EU	Notes	Skin
Austria	MAK (mg/m³)	221 mg/m³ (H)
Austria	MAK (ppm)	50 ppm (H)
Austria	MAK Short time value (mg/m³)	442 mg/m³ max. 4x15 min./Schicht, (H)
Austria	MAK Short time value (ppm)	100 ppm max. 4x15 min./Schicht, (H)
Belgium	Limit value (mg/m³)	221 mg/m³
Belgium	Limit value (ppm)	50 ppm
Belgium	Short time value (mg/m³)	442 mg/m³
Belgium	Short time value (ppm)	100 ppm
Belgium	Remark (BE)	D
Czech Republic	Local name	Xylen technická sm s isomer a (všechny isomery)
Czech Republic	Expoziční limity (PEL) (mg/m³)	200 mg/m³
Czech Republic	Expoziční limity (PEL) (ppm)	46 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m³)	400 mg/m³
Czech Republic	Expoziční limity (NPK-P) (ppm)	92 ppm
Czech Republic	Remark (CZ)	D,I

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Xylenes (1330-20-7)		
Denmark	Local name	Xylen (Dimethylbenzen), alle isomere
Denmark	Grænseværdie (langvarig) (mg/m³)	109 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	25 ppm
Denmark	Grænseværdie (kortvarig) (mg/m³)	218 mg/m³
Denmark	Grænseværdie (kortvarig) (ppm)	50 ppm
Denmark	Anmærkninger (DK)	H
Finland	Local name	Ksyleeni
Finland	HTP-arvo (8h) (mg/m³)	220 mg/m³
Finland	HTP-arvo (8h) (ppm)	50 ppm
Finland	HTP-arvo (15 min)	440 mg/m³
Finland	HTP-arvo (15 min) (ppm)	100 ppm
Finland	Huomautus (FI)	iho
France	Local name	Xylène, isomères mixtes, purs
France	VME (mg/m³)	221 mg/m³
France	VME (ppm)	50 ppm
France	VLE (mg/m³)	442 mg/m³
France	VLE (ppm)	100 ppm
Germany	TRGS 900 Local name	Xylol (alle Isomeren)
Germany	Occupational exposure limit value (mg/m³)	440 mg/m³
Germany	Occupational exposure limit value (ppm)	100 ppm
Germany	TRGS 900 Remark	H
Germany	TRGS 910 Acceptable concentration notes	
Hungary	Local name	XILOL(ok)
Hungary	AK-érték	221 mg/m³
Hungary	CK-érték	442 mg/m³
Ireland	OEL (8 hours ref) (mg/m³)	221 mg/m³
Ireland	OEL (8 hours ref) (ppm)	50 ppm
Ireland	OEL (15 min ref) (mg/m³)	442 mg/m³
Ireland	OEL (15 min ref) (ppm)	100 ppm
Ireland	Notes (IE)	Sk, IOELV
Italy	Local name	Xilene, isomeri misti, puro
Italy	OEL TWA (mg/m³)	221 mg/m³
Italy	OEL TWA (ppm)	50 ppm
Italy	OEL STEL (mg/m³)	442 mg/m³
Italy	OEL STEL (ppm)	100 ppm
Latvia	Local name	Ksilols (o-,m-,p-ksilols, dimetilbenzols)
Latvia	OEL TWA (mg/m³)	221 mg/m³
Latvia	OEL TWA (ppm)	50 ppm
Latvia	OEL STEL (mg/m³)	442 mg/m³
Latvia	OEL STEL (ppm)	100 ppm
Lithuania	IPRV (mg/m³)	200 mg/m³
Lithuania	IPRV (ppm)	50 ppm
Lithuania	TPRV (mg/m³)	450 mg/m³
Lithuania	TPRV (ppm)	100 ppm

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Xylenes (1330-20-7)		
Lithuania	Remark (LT)	O
Netherlands	Local name	Xyleen, o-, m-, p-isomeren
Netherlands	Grenswaarde TGG 8H (mg/m³)	210 mg/m³
Netherlands	Grenswaarde TGG 8H (ppm)	50 ppm
Netherlands	Grenswaarde TGG 15MIN (mg/m³)	442 mg/m³
Netherlands	Remark (MAC)	(H)
Poland	Local name	Ksilen mieszanina izomerów: 1,2-; 1,3-; 1,4-
Poland	NDS (mg/m³)	100 mg/m³
Poland	NDSch (mg/m³)	350 mg/m³
Portugal	Local name	Xileno (isómeros)
Portugal	OEL TWA (ppm)	100 ppm
Portugal	OEL STEL (ppm)	150 ppm
Slovakia	Local name	Xylén, zmiešané izoméry
Slovakia	NPHV (priemerná) (mg/m³)	221 mg/m³ (K)
Slovakia	NPHV (priemerná) (ppm)	50 ppm (K) 1.5 ppm (Xylén) 2000 ppm (Suma kyselín 2,3,4-metylhippurových)
Slovakia	OEL STEL (mg/m³)	442 mg/m³
Slovakia	OEL STEL (ppm)	100 ppm
Slovenia	Local name	ksilen (mešane izomere)
Slovenia	OEL TWA (mg/m³)	221 mg/m³
Slovenia	OEL TWA (ppm)	50 ppm
Slovenia	OEL STEL (mg/m³)	442 mg/m³
Slovenia	OEL STEL (ppm)	100 ppm
Spain	Local name	Xilenos, mezcla isómeros
Spain	VLA-ED (mg/m³)	221 mg/m³ vía dérmica,VLB, VLI
Spain	VLA-ED (ppm)	50 ppm vía dérmica,VLB, VLI 1.5 ppm (Ácidos metilhipúricos en orina; Final de la jornada laboral 2)
Spain	VLA-EC (mg/m³)	442 mg/m³ vía dérmica,VLB, VLI
Spain	VLA-EC (ppm)	100 ppm vía dérmica,VLB, VLI
Sweden	Local name	Xylen
Sweden	nivågränsvärde (NVG) (mg/m³)	221 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	442 mg/m³
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Sweden	Anmärkning (SE)	(H)
United Kingdom	WEL TWA (mg/m³)	220 mg/m³ (Sk)
United Kingdom	WEL TWA (ppm)	50 ppm (Sk) 650 ppm (methyl hippuric acid/mol creatinine in urine, Post shift)
United Kingdom	WEL STEL (mg/m³)	441 mg/m³ (Sk)
United Kingdom	WEL STEL (ppm)	100 ppm (Sk)
Norway	Local name	Xylen (alle isomere)
Norway	Grenseverdier (AN) (mg/m³)	108 mg/m³
Norway	Grenseverdier (AN) (ppm)	25 ppm
Norway	Merknader (NO)	H

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Xylenes (1330-20-7)		
Switzerland	VME (mg/m ³)	435 mg/m ³
Switzerland	MAK (ppm)	100 ppm 1.5 ppm Methylhippur-(Tolur-)säure (urina; in caso di esposizione per molto tempo/fine dell'esposizione / del turno) 1.5 ppm xilolo (sangue; fine dell'esposizione / del turno)
Switzerland	KZGW (mg/m ³)	870 mg/m ³ max. 4x30 min./turno
Switzerland	KZGW (ppm)	200 ppm max. 4x30 min./turno

trans-dichloroethylene (156-60-5)		
Austria	MAK (mg/m ³)	790 mg/m ³
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m ³)	3160 mg/m ³ max. 4x15 min./Schicht
Austria	MAK Short time value (ppm)	800 ppm max. 4x15 min./Schicht
Denmark	Local name	trans-Dichlorethen
Denmark	Grænseværdie (langvarig) (mg/m ³)	790 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Denmark	Grænseværdie (kortvarig) (mg/m ³)	1580 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	400 ppm
Denmark	Regulatory reference	BEK nr 655 af 31/05/2018
Finland	Local name	trans-Dikloorietyleni
Finland	HTP-arvo (8h) (mg/m ³)	800 mg/m ³
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	1000 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	250 ppm
Finland	Regulatory reference	HTP-ARVOT 2018 (Sosiaali- ja terveysministeriö)
Germany	TRGS 910 Acceptable concentration notes	
Poland	Local name	1,2-Dichloroeten – izomery trans-
Poland	NDS (mg/m ³)	700 mg/m ³
Poland	Regulatory reference	Dz. U. 2018 poz. 1286
Portugal	Local name	1,2-Dicloroetileno, todos os isómeros
Portugal	OEL TWA (ppm)	200 ppm
Slovakia	Regulatory reference	Norma Portuguesa NP 1796:2014
Slovenia	Local name	trans-dikloroeten
Slovenia	OEL TWA (mg/m ³)	800 mg/m ³
Slovenia	OEL TWA (ppm)	200 ppm
Slovenia	OEL STEL (mg/m ³)	1600 mg/m ³
Slovenia	OEL STEL (ppm)	400 ppm
Slovenia	Regulatory reference	Uradni list RS, št. 78/2018 z dne 4.12.2018
Switzerland	VME (mg/m ³)	790 mg/m ³
Switzerland	MAK (ppm)	200 ppm
Switzerland	KZGW (mg/m ³)	1580 mg/m ³
Switzerland	KZGW (ppm)	400 ppm

Isopropanol (67-63-0)		
Austria	MAK (mg/m ³)	500 mg/m ³

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Isopropanol (67-63-0)		
Austria	MAK (ppm)	200 ppm
Austria	MAK Short time value (mg/m³)	2000 mg/m³ max. 4x15 min./Schicht
Austria	MAK Short time value (ppm)	800 ppm max. 4x15 min./Schicht
Belgium	Limit value (mg/m³)	500 mg/m³
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m³)	1000 mg/m³
Belgium	Short time value (ppm)	400 ppm
Czech Republic	Local name	iso-Propanol
Czech Republic	Expoziční limity (PEL) (mg/m³)	500 mg/m³
Czech Republic	Expoziční limity (PEL) (ppm)	203.5 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m³)	1000 mg/m³
Czech Republic	Expoziční limity (NPK-P) (ppm)	407 ppm
Czech Republic	Remark (CZ)	I
Denmark	Local name	Isopropylalkohol (Isopropanol; 2-Propanol; sec-Propylalkohol)
Denmark	Grænseværdie (langvarig) (mg/m³)	490 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Denmark	Grænseværdie (kortvarig) (mg/m³)	980 mg/m³
Denmark	Grænseværdie (kortvarig) (ppm)	400 ppm
Finland	Local name	2-Propanoli
Finland	HTP-arvo (8h) (mg/m³)	500 mg/m³
Finland	HTP-arvo (8h) (ppm)	200 ppm
Finland	HTP-arvo (15 min)	620 mg/m³
Finland	HTP-arvo (15 min) (ppm)	250 ppm
France	Local name	Alcool isopropylique
France	VLE (mg/m³)	980 mg/m³
France	VLE (ppm)	400 ppm
Germany	TRGS 900 Local name	Propan-2-ol
Germany	Occupational exposure limit value (mg/m³)	500 mg/m³
Germany	Occupational exposure limit value (ppm)	200 ppm
Germany	TRGS 903 Biological limit value	50 mg/l Aceton (Blut; Expositionsende bzw. Schichtende)
Germany	TRGS 910 Acceptable concentration notes	
Hungary	Local name	IZOPROPIL-ALKOHOL
Hungary	AK-érték	500 mg/m³
Hungary	CK-érték	2000 mg/m³
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Ireland	Notes (IE)	Sk
Latvia	Local name	Izopropanols (2-propanols, izopropilspirts, 1-metil-1-etanols)
Latvia	OEL TWA (mg/m³)	350 mg/m³
Latvia	OEL STEL (mg/m³)	600 mg/m³
Lithuania	IPRV (mg/m³)	350 mg/m³
Lithuania	IPRV (ppm)	150 ppm
Lithuania	TPRV (mg/m³)	600 mg/m³

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Isopropanol (67-63-0)		
Lithuania	TPRV (ppm)	250 ppm
Netherlands	Grenswaarde TGG 8H (mg/m³)	650 mg/m³
Netherlands	Grenswaarde TGG 8H (ppm)	250 ppm
Poland	Local name	Propan-2-ol (izopropylowy alkohol)
Poland	NDS (mg/m³)	900 mg/m³
Poland	NDSch (mg/m³)	1200 mg/m³
Portugal	Local name	2-Propanol (isopropanol ou álcool isopropílico)
Portugal	OEL TWA (ppm)	200 ppm
Portugal	OEL STEL (ppm)	400 ppm
Slovakia	Local name	Izopropylalkohol (propán-2-ol)
Slovakia	NPHV (priemerná) (mg/m³)	500 mg/m³
Slovakia	NPHV (priemerná) (ppm)	200 ppm
Slovakia	OEL STEL (mg/m³)	1000 mg/m³
Slovakia	OEL STEL (ppm)	400 ppm
Slovenia	Local name	propan-2-ol (izopropilalkohol; izopropanol)
Slovenia	OEL TWA (mg/m³)	500 mg/m³
Slovenia	OEL TWA (ppm)	200 ppm
Slovenia	OEL STEL (mg/m³)	2000 mg/m³
Slovenia	OEL STEL (ppm)	800 ppm
Spain	Local name	Isopropanol (Alcohol isopropílico)
Spain	VLA-ED (mg/m³)	500 mg/m³ VLB, s
Spain	VLA-ED (ppm)	200 ppm VLB, s 40 ppm F, I "(Acetona en orina; Final de la semana, laboral 1)"
Spain	VLA-EC (mg/m³)	1000 mg/m³ VLB, s
Spain	VLA-EC (ppm)	400 ppm VLB, s
Sweden	Local name	Isopropanol
Sweden	nivågränsvärde (NVG) (mg/m³)	350 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	150 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	600 mg/m³
Sweden	kortidsvärde (KTV) (ppm)	250 ppm
United Kingdom	WEL TWA (mg/m³)	999 mg/m³
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m³)	1250 mg/m³
United Kingdom	WEL STEL (ppm)	500 ppm
Norway	Local name	2-propanol (Isopropanol)
Norway	Grenseverdier (AN) (mg/m³)	245 mg/m³
Norway	Grenseverdier (AN) (ppm)	100 ppm
Switzerland	VME (mg/m³)	500 mg/m³
Switzerland	MAK (ppm)	200 ppm 25 ppm acetone (urina; fine dell'esposizione / del turno) 25 ppm acetone (sangue; fine dell'esposizione / del turno)
Switzerland	KZGW (mg/m³)	1000 mg/m³ max. 4x15 min./turno
Switzerland	KZGW (ppm)	400 ppm max. 4x15 min./turno

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)		
EU	Local name	2-(2-Butoxyethoxy)ethanol
EU	IOELV TWA (mg/m³)	67.5 mg/m³
EU	IOELV TWA (ppm)	10 ppm
EU	IOELV STEL (mg/m³)	101.2 mg/m³
EU	IOELV STEL (ppm)	15 ppm
EU	Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Austria	MAK (mg/m³)	67.5 mg/m³
Austria	MAK (ppm)	10 ppm
Austria	MAK Short time value (mg/m³)	101.2 mg/m³ max. 4x15 min./Schicht
Austria	MAK Short time value (ppm)	15 ppm max. 4x15 min./Schicht
Belgium	Limit value (mg/m³)	67.5 mg/m³
Belgium	Limit value (ppm)	10 ppm
Belgium	Short time value (mg/m³)	101.2 mg/m³
Belgium	Short time value (ppm)	15 ppm
Czech Republic	Local name	2-(2-Buthoxyethoxy)ethanol (Butyldiglykol)
Czech Republic	Expoziční limity (PEL) (mg/m³)	70 mg/m³
Czech Republic	Expoziční limity (PEL) (ppm)	10.6 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m³)	100 mg/m³
Czech Republic	Expoziční limity (NPK-P) (ppm)	15 ppm
Czech Republic	Remark (CZ)	I (dráždí sliznice (oči, dýchací cesty) resp. kůži)
Czech Republic	Regulatory reference	Nařízení vlády č. 361/2007 Sb. (zpracovány změny č. 246/2018 Sb.)
Denmark	Local name	Butyldiglycol
Denmark	Grænseværdie (langvarig) (mg/m³)	68 mg/m³
Denmark	Grænseværdie (langvarig) (ppm)	10 ppm
Denmark	Anmærkninger (DK)	E (betyder, at stoffet har en EF-grænseværdi)
Denmark	Regulatory reference	BEK nr 655 af 31/05/2018
Finland	Local name	2-(2-Butoksietoksi)etanoli
Finland	HTP-arvo (8h) (mg/m³)	68 mg/m³
Finland	HTP-arvo (8h) (ppm)	10 ppm
Finland	Regulatory reference	HTP-ARVOT 2018 (Sosiaali- ja terveystieteiden ministeriö)
France	Local name	2-(2-butoxyethoxy)éthanol
France	VME (mg/m³)	67.5 mg/m³
France	VME (ppm)	10 ppm
France	VLE (mg/m³)	101.2 mg/m³
France	VLE (ppm)	15 ppm
France	Note (FR)	Valeurs réglementaires indicatives
France	Regulatory reference	Arrêté du 30 juin 2004 modifié (réf.: INRS ED 984, 2016)
Germany	TRGS 900 Local name	2-(2-Butoxyethoxy)ethanol
Germany	Occupational exposure limit value (mg/m³)	67 mg/m³
Germany	Occupational exposure limit value (ppm)	10 ppm
Germany	Limitation of exposure peaks	1,5(l)
Germany	TRGS 900 Remark	EU;DFG;Y;11
Germany	TRGS 900 Regulatory reference	TRGS900

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)		
Germany	TRGS 910 Acceptable concentration notes	
Hungary	Local name	2-(2-BUTOXIETOXI)ETANOL
Hungary	AK-érték	67.5 mg/m ³
Hungary	CK-érték	101.2 mg/m ³
Hungary	Megjegyzések (HU)	EU2 (2006/15/EK irányelvben közölt érték)
Hungary	Regulatory reference	25/2000. (IX. 30.) EüM–SZCSM együttes rendelet a munkahelyek kémiai biztonságáról
Ireland	OEL (8 hours ref) (mg/m ³)	67.5 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	10 ppm
Ireland	OEL (15 min ref) (mg/m ³)	101.2 mg/m ³
Ireland	OEL (15 min ref) (ppm)	15 ppm
Ireland	Notes (IE)	IOELV
Italy	Local name	2-(2-Butossietossi)etanolo
Italy	OEL TWA (mg/m ³)	67.5 mg/m ³
Italy	OEL TWA (ppm)	10 ppm
Italy	OEL STEL (mg/m ³)	101.2 mg/m ³
Italy	OEL STEL (ppm)	15 ppm
Italy	Regulatory reference	Allegato XXXVIII del D.Lgs. 9 aprile 2008, n. 81 e s.m.i.
Latvia	Local name	2-(2-Butoksietoksi) etanols (butildiglikols)
Latvia	OEL TWA (mg/m ³)	67.5 mg/m ³
Latvia	OEL TWA (ppm)	10 ppm
Latvia	OEL STEL (mg/m ³)	101.2 mg/m ³
Latvia	OEL STEL (ppm)	15 ppm
Latvia	Regulatory reference	Ministru kabineta 2007.gada 15.maija noteikumiem Nr.325 (Grozījumi Ministru kabineta 2011.gada 1.februārī noteikumiem Nr.92)
Lithuania	IPRV (mg/m ³)	100 mg/m ³
Lithuania	IPRV (ppm)	15 ppm
Lithuania	TPRV (mg/m ³)	200 mg/m ³
Lithuania	TPRV (ppm)	30 ppm
Netherlands	Local name	2-(2-Butoxyethoxy)ethanol
Netherlands	Grenswaarde TGG 8H (mg/m ³)	50 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	100 mg/m ³
Netherlands	Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Netherlands	Regulatory reference	Arbeidsomstandighedenregeling 2018
Poland	Local name	2-(2-Butoksyetoksy)etanol
Poland	NDS (mg/m ³)	67 mg/m ³
Poland	NDSch (mg/m ³)	100 mg/m ³
Poland	Regulatory reference	Dz. U. 2018 poz. 1286
Portugal	Local name	2-(2-ButoxiETOXI) etanol (éter dietilenoglicol monobutílico)
Portugal	OEL TWA (ppm)	10 ppm FIV (Fração inalável e vapor)

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)		
Slovakia	Regulatory reference	Norma Portuguesa NP 1796:2014
Slovakia	Local name	Butyldiglykol 2-(2-butoxyetoxy)etanol
Slovakia	NPHV (priemerná) (mg/m³)	67.5 mg/m³
Slovakia	NPHV (priemerná) (ppm)	10 ppm
Slovakia	OEL STEL (mg/m³)	101.2 mg/m³
Slovakia	OEL STEL (ppm)	15 ppm
Slovakia	Regulatory reference	Nariadenie vlády č. 33/2018 Z.z.
Slovenia	Local name	2-(2-butoksietoksi)etanol (butildietilenglikol)
Slovenia	OEL TWA (mg/m³)	67.5 mg/m³
Slovenia	OEL TWA (ppm)	10 ppm
Slovenia	OEL STEL (mg/m³)	101.2 mg/m³
Slovenia	OEL STEL (ppm)	15 ppm
Slovenia	Remark (SI)	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti), EU
Slovenia	Regulatory reference	Uradni list RS, št. 78/2018 z dne 4.12.2018
Spain	Local name	2-(2-Butoxietoxi) etanol (Dietilenglicol monobutiléter)
Spain	VLA-ED (mg/m³)	67.5 mg/m³
Spain	VLA-ED (ppm)	10 ppm
Spain	VLA-EC (mg/m³)	101.2 mg/m³
Spain	VLA-EC (ppm)	15 ppm
Spain	Notes	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Spain	Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
Sweden	Local name	Dietylenglykolmonobutyleter
Sweden	nivågränsvärde (NVG) (mg/m³)	68 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	10 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	101 mg/m³
Sweden	kortidsvärde (KTV) (ppm)	15 ppm
Sweden	Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom	WEL TWA (mg/m³)	67.5 mg/m³
United Kingdom	WEL TWA (ppm)	10 ppm
United Kingdom	WEL STEL (mg/m³)	101.2 mg/m³
United Kingdom	WEL STEL (ppm)	15 ppm
Norway	Local name	2-2(butoksyetoksi)etanol
Norway	Grenseverdier (AN) (mg/m³)	68 mg/m³
Norway	Grenseverdier (AN) (ppm)	10 ppm
Norway	Merknader (NO)	E (EU har en veiledende grenseverdi for stoffet)
Norway	Regulatory reference	FOR-2018-08-21-1255

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)

Switzerland	VME (mg/m ³)	67 mg/m ³
Switzerland	MAK (ppm)	10 ppm
Switzerland	KZGW (mg/m ³)	101.2 mg/m ³ max. 4x15 min./turno
Switzerland	KZGW (ppm)	15 ppm max. 4x15 min./turno

Benzene (71-43-2)

EU	Local name	Benzene
EU	IOELV TWA (mg/m ³)	3.25 mg/m ³
EU	IOELV TWA (ppm)	1 ppm
EU	Notes	Skin (Substantial contribution to the total body burden via dermal exposure possible)
EU	European BLV	28 µg/l Parameter: benzene - Medium: blood - Sampling time: immediately end of shift 46 µg/g creatinine Parameter: phenylmercapturic - Medium: urine - Sampling time: end of exposure/shift
EU	Regulatory reference	DIRECTIVE (EU) 2019/130 (amending Directive 2004/37/EC)
Austria	MAK (mg/m ³)	3.2 mg/m ³ (H, III A1)
Austria	MAK (ppm)	1 ppm (H, III A1)
Austria	MAK Short time value (mg/m ³)	12.8 mg/m ³ (H, III A1) max. 4x15 min./Schicht
Austria	MAK Short time value (ppm)	4 ppm (H, III A1) max. 4x15 min./Schicht
Belgium	Limit value (mg/m ³)	3.25 mg/m ³
Belgium	Limit value (ppm)	1 ppm
Belgium	Remark (BE)	C, D
Czech Republic	Local name	Benzen
Czech Republic	Expoziční limity (PEL) (mg/m ³)	3 mg/m ³
Czech Republic	Expoziční limity (PEL) (ppm)	0.94 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m ³)	10 mg/m ³
Czech Republic	Expoziční limity (NPK-P) (ppm)	3.1 ppm
Czech Republic	Remark (CZ)	D (při expozici se významně uplatňuje pronikání látky kůží), I (dráždí sliznice (oči, dýchací cesty) resp. kůží), P (u látky nelze vyloučit závažné pozdní účinky)
Czech Republic	Czech Republic - BLV	0.05 mg/g creatinine Ukazatel: S-Fenylmerkapturová kyselina - Biološki uzorak: moči - Doba odběru: konec směny 0.024 µmol/mmol Creatinine Ukazatel: S-Fenylmerkapturová kyselina - Biološki uzorak: moči - Doba odběru: konec směny 1.5 mg/g creatinine Ukazatel: t,t-Mukonová kyselina - Biološki uzorak: moči - Doba odběru: konec směny 1.2 µmol/mmol Creatinine Ukazatel: t,t-Mukonová kyselina - Biološki uzorak: moči - Doba odběru: konec směny
Czech Republic	Regulatory reference	Nařízení vlády č. 361/2007 Sb. (zpracovány změny č. 246/2018 Sb.)
Denmark	Local name	Benzen
Denmark	Grænseværdie (langvarig) (mg/m ³)	1.6 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	0.5 ppm
Denmark	Grænseværdie (kortvarig) (mg/m ³)	3.2 mg/m ³
Denmark	Grænseværdie (kortvarig) (ppm)	1 ppm

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Benzene (71-43-2)		
Denmark	Anmærkninger (DK)	E (betyder, at stoffet har en EF-grænseværdi); H (betyder, at stoffet kan optages gennem huden); K (betyder, at stoffet anses for at kunne være kræftfremkaldende)
Denmark	Regulatory reference	BEK nr 655 af 31/05/2018
Finland	Local name	Bentseeni
Finland	HTP-arvo (8h) (mg/m ³)	3.25 mg/m ³
Finland	HTP-arvo (8h) (ppm)	1 ppm
Finland	Huomautus (FI)	iho, Valtioneuvosto on työturvallisuuslain nojalla antamissaan päätöksissä ja asetuksissa määrännyt työpaikan ilman epäpuhtauksille joukon sitovia raja-arvoja. Soveltamisala: Kaikki työt. Viite: Valtioneuvoston asetus työhön liittyvän syöpävaaran torjunnasta (716/2000), Bentseeni voi imeytyä elimistöön hengitysteitse, ihon kautta tai nieltynä. Se saattaa aiheuttaa syöpää. Bentseeni saattaa aiheuttaa myös perimävaurioita, joten siihen tulee suhtautua siten kuin se aiheuttaisi periytyviä mutaatioita ihmisen sukusoluissa. Se vahingoittaa elimiä a voi tappaa nieltynä ja joutuessaan iholle. Lisäksi se ärsyttää silmiä ja ihoa. Haju ei varoita terveysvaarasta.
Finland	Regulatory reference	HTP-ARVOT 2018 (Sosiaali- ja terveysministeriö)
France	Local name	Benzène
France	VME (mg/m ³)	3.25 mg/m ³
France	VME (ppm)	1 ppm
France	Note (FR)	Valeurs réglementaires contraignantes; risque de pénétration percutanée
France	Regulatory reference	Article R4412-149 du Code du travail (réf.: INRS ED 984, 2016; Décret n° 2019-1487)
Germany	TRGS 910 Acceptable concentration notes	
Hungary	Local name	BENZOL
Hungary	MK-érték	3 mg/m ³
Hungary	Megjegyzések (HU)	k (rákkeltő), b (Bőrön át is felszívódik), i (ingerlő anyag, amely izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát); EU99 (99/38/EK irányelvben közölt érték), BEM (biológiai expozíciós mutató)
Hungary	Regulatory reference	25/2000. (IX. 30.) EüM–SZCSM együttes rendelet a munkahelyek kémiai biztonságáról
Ireland	OEL (8 hours ref) (mg/m ³)	3 mg/m ³
Ireland	OEL (8 hours ref) (ppm)	1 ppm
Ireland	Notes (IE)	Sk, C1
Latvia	Local name	Benzols
Latvia	OEL TWA (mg/m ³)	3.25 mg/m ³
Latvia	OEL TWA (ppm)	1 ppm
Latvia	Latvia - BLV	25 µg/g creatinine Urīnā maiņas beigās nosaka fenolu
Latvia	Regulatory reference	Ministru kabineta 2007.gada 15.maija noteikumiem Nr.325
Lithuania	IPRV (mg/m ³)	3.25 mg/m ³
Lithuania	IPRV (ppm)	1 ppm
Lithuania	TPRV (mg/m ³)	19 mg/m ³
Lithuania	TPRV (ppm)	6 ppm
Lithuania	Remark (LT)	K O; IPRV 3,25mg/m3 (1 ppm) galios nuo 2003 06 27 (pagal direktyvos 97/42 EC 2 str. 1 dalyje nurodytą datą).

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Benzene (71-43-2)		
Netherlands	Local name	Benzeen
Netherlands	Grenswaarde TGG 8H (mg/m³)	3.25 mg/m³
Netherlands	Remark (MAC)	H (Huidopname) Stoffen die relatief gemakkelijk door de huid kunnen worden opgenomen, hetgeen een substantiële bijdrage kan betekenen aan de totale inwendige blootstelling, hebben in de lijst een H-aanduiding. Bij deze stoffen moeten naast maatregelen tegen inademing ook adequate maatregelen ter voorkoming van huidcontact worden genomen.
Netherlands	Regulatory reference	Arbeidsomstandighedenregeling 2018
Poland	Local name	Benzen
Poland	NDS (mg/m³)	1.6 mg/m³
Poland	Remark (PL)	Skóra (Oznakowanie substancji notacją „skóra” oznacza, że wchłanianie substancji przez skórę może być tak samo istotne jak przy narażeniu drogą oddechową)
Poland	Regulatory reference	Dz. U. 2018 poz. 1286
Portugal	Local name	Benzeno
Portugal	OEL TWA (ppm)	0.5 ppm
Portugal	OEL STEL (ppm)	2.5 ppm
Portugal	Portugal (BEI)	25 µg/g creatinine Parâmetro: Ácido s-fenilmercaptúrico - Meio: urina - Momento da amostragem: Fim do turno - Notação: Vb (Valor basal) 500 µg/g creatinine Parâmetro: Ácido t,t-mucónico - Meio: urina - Momento da amostragem: Fim do turno - Notação: Vb (Valor basal)
Slovakia	Regulatory reference	Norma Portuguesa NP 1796:2014
Slovakia	Local name	benzén
Slovakia	NPHV (priemerná) (mg/m³)	1 mg/m³
Slovakia	NPHV (priemerná) (ppm)	3.25 ppm
Slovakia	Upozornenie (SK)	Kategória karcinogénov 1A – Dokázaný karcinogén pre ľudí; Kategória karcinogénov 1B – Mutagén cicavčích zárodočných buniek; Prienik cez pokožku (Niektoré látky môžu prenikať ľahko cez pokožku a spôsobovať smrteľné otravy často bez varovných príznakov)
Slovakia	Regulatory reference	Nariadenie vlády č. 83/2015 Z. z.
Slovenia	Local name	benzen
Slovenia	OEL TWA (mg/m³)	3.25 mg/m³
Slovenia	OEL TWA (ppm)	1 ppm
Slovenia	OEL STEL (mg/m³)	13 mg/m³
Slovenia	OEL STEL (ppm)	4 ppm
Spain	Local name	Benceno
Spain	VLA-ED (mg/m³)	3.25 mg/m³
Spain	VLA-ED (ppm)	1 ppm

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Benzene (71-43-2)		
Spain	Notes	C1A (Carcinógeno para el hombre), M1B (Sustancias de las que se considera que inducen mutaciones hereditarias en las células germinales humanas), vía dérmica (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante), VLB® (Agente químico que tiene Valor Límite Biológico), v (Real Decreto 1124/2000, de 16 de junio (BOE nº 145 de 17 de junio de 2000), por el que se modifica el Real Decreto 665/1997, de 12 de mayo, sobre la protección de los trabajadores contra los riesgos relacionados con la exposición a agentes cancerígenos durante el trabajo), r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) nº 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Spain		0.045 mg/g creatinine Parámetro: Ácido S-Fenilmercaptúrico - Medio: Orina - Momento de muestreo: Final de la jornada laboral 2 mg/l Parámetro: Ácido t,t-Mucónico - Medio: Orina - Momento de muestreo: Final de la jornada laboral
Spain	Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
Sweden	Local name	Bensen
Sweden	nivågränsvärde (NVG) (mg/m³)	1.5 mg/m³
Sweden	nivågränsvärde (NVG) (ppm)	0.5 ppm
Sweden	kortidsvärde (KTV) (mg/m³)	9 mg/m³
Sweden	kortidsvärde (KTV) (ppm)	3 ppm
Sweden	Anmärkning (SE)	C (Ämnet är cancerframkallande. Risk för cancer finns även vid annan exponering än via inandning. För vissa cancerframkallande ämnen som inte har gränsvärden gäller förbud eller tillståndskrav enligt föreskrifterna om kemiska arbetsmiljörisker); H (Ämnet kan lätt upptas genom huden. Det föreskrivna gränsvärdet bedöms ge tillräckligt skydd endast under förutsättning att huden är skyddad mot exponering för ämnet ifråga)
Sweden	Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom	WEL TWA (mg/m³)	3.25 mg/m³
United Kingdom	WEL TWA (ppm)	1 ppm
United Kingdom	Remark (WEL)	Carc, Sk
Norway	Local name	Benzen
Norway	Grenseverdier (AN) (mg/m³)	3 mg/m³
Norway	Grenseverdier (AN) (ppm)	1 ppm
Norway	Merknader (NO)	G (EU har fastsatt en bindende grenseverdi for stoffet); H (Kjemikalier som kan tas opp gjennom huden); K (Kjemikalier som skal betraktes som kreftfremkallende)
Norway	Regulatory reference	FOR-2018-08-21-1255
Switzerland	VME (mg/m³)	1.6 mg/m³

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Benzene (71-43-2)

Switzerland	MAK (ppm)	0.5 ppm 25 ppm S-Phenylmerkaptursäure, Urin, b, 500 ppm t,t-Mukonsäure, Urin, b
-------------	-----------	---

Carbon black (1333-86-4)

Belgium	Limit value (mg/m³)	3.5 mg/m³
Denmark	Local name	Carbon black
Denmark	Grænseværdie (langvarig) (mg/m³)	3.5 mg/m³
Denmark	Anmærkninger (DK)	K (betyder, at stoffet anses for at kunne være kræftfremkaldende)
Denmark	Regulatory reference	BEK nr 655 af 31/05/2018
Finland	Local name	Nokimusta
Finland	HTP-arvo (8h) (mg/m³)	3.5 mg/m³
Finland	HTP-arvo (15 min)	7 mg/m³
Finland	Regulatory reference	HTP-ARVOT 2018 (Sosiaali- ja terveystieteiden ministeriö)
France	Local name	Noir de carbone
France	VME (mg/m³)	3.5 mg/m³
France	Note (FR)	Valeurs recommandées/admises
France	Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany	TRGS 910 Acceptable concentration notes	
Ireland	OEL (8 hours ref) (mg/m³)	3.5 mg/m³
Ireland	OEL (15 min ref) (mg/m³)	7 mg/m³
Poland	Local name	Sadza techniczna
Poland	NDS (mg/m³)	4 mg/m³ frakcja wdychalna
Poland	Remark (PL)	Frakcja wdychalna – frakcja aerozolu wnikać przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia.
Poland	Regulatory reference	Dz. U. 2018 poz. 1286
Portugal	Local name	Carbono, preto (Negro de fumo)
Portugal	OEL TWA (mg/m³)	3 mg/m³ I (Fração inalável)
Slovakia	Regulatory reference	Norma Portuguesa NP 1796:2014
Spain	Local name	Negro de humo
Spain	VLA-ED (mg/m³)	3.5 mg/m³
Spain	Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2019. INSHT
Sweden	Local name	Kimrök
Sweden	nivågränsvärde (NVG) (mg/m³)	3 mg/m³
Sweden	Anmärkning (SE)	2 (Med totaldamm menas de partiklar (aerosoler) som fastnar på ett filter i den provtagare som beskrivs i Metodserien, Provtagnings av totaldamm och respirabelt damm, Metod nr 1010, Arbetsmiljöverket, numera Arbetsmiljöverket. Filterdiameteren är normalt 37 mm, men kan även vara 25 mm. Trots sitt namn provtas inte den totala mängden luftburna partiklar med denna metod)
United Kingdom	Local name	Carbon black
United Kingdom	WEL TWA (mg/m³)	3.5 mg/m³
United Kingdom	WEL STEL (mg/m³)	7 mg/m³
Norway	Local name	Carbon Black (lampesot)

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Carbon black (1333-86-4)

Norway	Grønseverdier (AN) (mg/m³)	3.5 mg/m³
Norway	Regulatory reference	FOR-2018-08-21-1255

8.2. Exposure controls

Appropriate engineering controls:

Avoid splashing. Avoid creating mist or spray. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Provide local exhaust or general room ventilation.

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear suitable gloves resistant to chemical penetration. neoprene/butyl rubber. EN 374

Eye protection:

Safety glasses with side guards should be worn to prevent injury from airborne particles and/or other eye contact with this product. EN 166

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of inadequate ventilation wear respiratory protection. Supplied air respirator if working in a confined area. EN 14594. Handling large quantities of product: Wear a self contained breathing apparatus. EN 137. EN 145

Environmental exposure controls:

Prevent leakage or spillage.

Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Opaque liquid.
Colour	: Blue. Gray.
Odour	: mild. characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 100 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: 1000 mm²/s
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Alkali metals. Alkaline earth metals. Powdered metallic salts. Strong bases.

10.6. Hazardous decomposition products

None under normal use. Under fire conditions, hazardous fumes will be present. Fluorinated hydrocarbons. Hydrogen fluoride. Carbon oxides (CO, CO₂). hydrogen chloride. Carbonyl fluoride.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)

Acute toxicity (inhalation) : Harmful if inhaled.

ATE (dust,mist)	2.449 mg/l/4h
-----------------	---------------

Phenolphthalein (77-09-8)

LD50 oral rat	> 2000 mg/kg bodyweight
---------------	-------------------------

29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)

LD50 oral rat	> 10000 mg/kg
---------------	---------------

LD50 dermal rat	> 5000 mg/kg
-----------------	--------------

ethylbenzene (100-41-4)

LD50 oral rat	3500 mg/kg
---------------	------------

LD50 dermal rabbit	17.8 ml/kg
--------------------	------------

LC50 inhalation rat (ppm)	< 1500 ppm
---------------------------	------------

Toluene (108-88-3)

LD50 oral rat	5580 mg/kg EU Method B.
---------------	-------------------------

LC50 inhalation rat (mg/l)	> 20 mg/l/4h OECD Guideline 403
----------------------------	---------------------------------

Xylenes (1330-20-7)

LD50 oral rat	> 3500 mg/kg
---------------	--------------

trans-dichloroethylene (156-60-5)

LD50 oral rat	7902 mg/kg
---------------	------------

LD50 dermal rabbit	> 5000 mg/kg
--------------------	--------------

LC50 inhalation rat (mg/l)	95.4 mg/l/4h
----------------------------	--------------

LC50 inhalation rat (Vapours - mg/l/4h)	24100 mg/l/4h
---	---------------

Isopropanol (67-63-0)

LD50 oral rat	5840 mg/kg
---------------	------------

LD50 dermal rabbit	16.4 ml/kg
--------------------	------------

LC50 inhalation rat (ppm)	> 10000 ppm/4h
---------------------------	----------------

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)

LD50 oral rat	4500 mg/kg
LD50 dermal rabbit	2700 mg/kg

Benzene (71-43-2)

LD50 oral rat	5970 mg/kg OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 9.4 mg/kg OECD Guideline 402 (Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	43.7 mg/l/4h OECD Guideline 403 (Acute Inhalation Toxicity)

1,1,1 Tris Ethane (27955-94-8)

LD50 oral rat	> 5000 mg/kg bodyweight
LD50 dermal rat	> 2000 mg/kg bodyweight

Carbon black (1333-86-4)

LD50 oral rat	> 8000 mg/kg
LC50 inhalation rat (mg/l)	> 4.6 mg/m ³ 4 h

Skin corrosion/irritation	: Not classified (Based on available data, the classification criteria are not met)
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Suspected of causing genetic defects.
Carcinogenicity	: May cause cancer.

Phenolphthalein (77-09-8)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

ethylbenzene (100-41-4)

IARC group	2B - Possibly carcinogenic to humans
------------	--------------------------------------

Toluene (108-88-3)

IARC group	3 - Not classifiable
------------	----------------------

Xylenes (1330-20-7)

IARC group	3 - Not classifiable
------------	----------------------

Isopropanol (67-63-0)

IARC group	3 - Not classifiable
------------	----------------------

Benzene (71-43-2)

IARC group	1 - Carcinogenic to humans
------------	----------------------------

Carbon black (1333-86-4)

IARC group	2B - Possibly carcinogenic to humans, Inhalation of dust
------------	--

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: Not classified (Based on available data, the classification criteria are not met)
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)

Toluene (108-88-3)

LOAEC (inhalation, rat, gas, 90 days)	1250 ppmv/6h/day
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight/day EU Method B.26.
NOAEC (inhalation, rat, gas, 90 days)	300 ppmv/6h/day OECD Guideline 453

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Benzene (71-43-2)

LOAEL (oral, rat, 90 days)	25 mg/kg bodyweight/day OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	100 mg/kg bodyweight/day OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, gas, 90 days)	30 ppmv/6h/day OECD Guideline 412 / 413

Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Viscosity, kinematic	1000 mm²/s
----------------------	------------

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

Phenolphthalein (77-09-8)

EC50 crustacea	> 100 mg/l
----------------	------------

29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)

LC50 fish 1	> 100 mg/l 96 h
EC50 crustacea	> 500 mg/l 48 h

ethylbenzene (100-41-4)

LC50 fish 1	5.1 mg/l
EC50 other aquatic organisms 1	7.7 mg/l
NOEC (acute)	3.3 mg/l

Toluene (108-88-3)

LC50 fish 1	5.5 mg/l
EC50 Daphnia 2	3.78 mg/l
ErC50 (algae)	134 mg/l
LOEC (chronic)	2.77 mg/l
NOEC chronic fish	1.39 mg/l
NOEC chronic crustacea	0.74 mg/l

trans-dichloroethylene (156-60-5)

LC50 fish 1	135 mg/l 96 h
EC50 crustacea	220 mg/l 48 h

Isopropanol (67-63-0)

LC50 fish 1	10000 mg/l
-------------	------------

2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether (112-34-5)

LC50 fish 1	2000 mg/l 96 hr- Menidia beryllina
-------------	------------------------------------

Benzene (71-43-2)

LC50 fish 1	5.3 mg/l OECD Guideline 203 (Fish, Acute Toxicity Test)
EC50 crustacea	10 mg/l OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

ErC50 (algae)	100 mg/l OECD Guideline 201 (Alga, Growth Inhibition Test)
LOEC (chronic)	1.6 mg/l 32 d
NOEC chronic crustacea	3 mg/l

12.2. Persistence and degradability

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)	
Persistence and degradability	May cause long-term adverse effects in the environment.

29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)	
Persistence and degradability	Readily biodegradable.

ethylbenzene (100-41-4)	
Persistence and degradability	Not established.

Toluene (108-88-3)	
Persistence and degradability	Readily biodegradable.

trans-dichloroethylene (156-60-5)	
Persistence and degradability	Readily biodegradable.
Biodegradation	95 % 28 d

Isopropanol (67-63-0)	
Persistence and degradability	Readily biodegradable.

Benzene (71-43-2)	
Persistence and degradability	Readily biodegradable.

1,1,1 Tris Ethane (27955-94-8)	
Persistence and degradability	Not readily biodegradable.
Biodegradation	8 %

Carbon black (1333-86-4)	
Persistence and degradability	Not readily biodegradable.

12.3. Bioaccumulative potential

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)	
Bioaccumulative potential	Not established.

Phenolphthalein (77-09-8)	
Log Kow	2.4

29H,31H-phthalocyaninato(2-)-N29,N30,N31,N32 copper (147-14-8)	
BCF fish 1	< 3.6

ethylbenzene (100-41-4)	
Bioaccumulative potential	Not established.

Toluene (108-88-3)	
Bioconcentration factor (BCF REACH)	90
Log Kow	2.73

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

Xylenes (1330-20-7)

BCF fish 1	1.3 mg/l
Bioaccumulative potential	Not expected to bioaccumulate.

trans-dichloroethylene (156-60-5)

Log Pow	2.06
---------	------

Isopropanol (67-63-0)

Bioaccumulative potential	Not expected to bioaccumulate.
---------------------------	--------------------------------

Benzene (71-43-2)

BCF fish 1	3.5 – 4.4
Bioconcentration factor (BCF REACH)	0
Log Pow	1.83

1,1,1 Tris Ethane (27955-94-8)

Log Kow	3.88
---------	------

12.4. Mobility in soil

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Ecology - soil	Not established.
----------------	------------------

12.5. Results of PBT and vPvB assessment

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

PBT: not yet assessed

vPvB: not yet assessed

Component

Phenolphthalein (77-09-8)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
---------------------------	---

12.6. Other adverse effects

Additional information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.
HP Code	: HP10 - "Toxic for reproduction:" waste which has adverse effects on sexual function and fertility in adult males and females, as well as developmental toxicity in the offspring. HP11 - "Mutagenic:" waste which may cause a mutation, that is a permanent change in the amount or structure of the genetic material in a cell. HP14 - "Ecotoxic:" waste which presents or may present immediate or delayed risks for one or more sectors of the environment HP4 - "Irritant — skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye. HP6 - "Acute Toxicity:" waste which can cause acute toxic effects following oral or dermal administration, or inhalation exposure. HP7 - "Carcinogenic:" waste which induces cancer or increases its incidence

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: Not regulated.
UN-No. (IMDG)	: Not regulated.
UN-No. (IATA)	: Not regulated.
UN-No. (ADN)	: Not regulated.

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

UN-No. (RID)	: Not regulated.
14.2. UN proper shipping name	
Proper Shipping Name (ADR)	: Not regulated.
Proper Shipping Name (IMDG)	: Not regulated.
Proper Shipping Name (IATA)	: Not regulated.
Proper Shipping Name (ADN)	: Not regulated.
Proper Shipping Name (RID)	: Not regulated.
14.3. Transport hazard class(es)	
ADR	
Transport hazard class(es) (ADR)	: Not regulated.
IMDG	
Transport hazard class(es) (IMDG)	: Not regulated.
IATA	
Transport hazard class(es) (IATA)	: Not regulated.
ADN	
Transport hazard class(es) (ADN)	: Not regulated.
RID	
Transport hazard class(es) (RID)	: Not regulated.
14.4. Packing group	
Packing group (ADR)	: Not regulated.
Packing group (IMDG)	: Not regulated.
Packing group (IATA)	: Not regulated.
Packing group (ADN)	: Not regulated.
Packing group (RID)	: Not regulated.
14.5. Environmental hazards	
Dangerous for the environment	: No
Marine pollutant	: No
Other information	: No supplementary information available
14.6. Special precautions for user	
Overland transport	
Not regulated.	
Transport by sea	
Not regulated.	
Air transport	
Not regulated.	
Inland waterway transport	
Not regulated.	
Rail transport	
Not regulated.	
14.7. Transport in bulk according to Annex II of Marpol and the IBC Code	
Not regulated.	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

28. Substances which are classified as carcinogen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 1 or Appendix 2, respectively.	Phenolphthalein ; Benzene
3(b) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10	ethylbenzene ; Toluene ; Xylenes ; Benzene ; 2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether ; Methyl nonafluoroisobutyl ether ; Methyl nonafluorobutyl ether ; trans-dichloroethylene ; Isopropanol
3(c) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1	Toluene ; trans-dichloroethylene
5. Benzene	Benzene

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

29. Substances which are classified as germ cell mutagen category 1A or 1B in Part 3 of Annex VI to Regulation (EC) No 1272/2008 and are listed in Appendix 3 or Appendix 4, respectively.	Benzene
3(a) Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	ethylbenzene ; Toluene ; Xylenes ; Benzene ; trans-dichloroethylene ; Isopropanol
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	ethylbenzene ; Toluene ; Xylenes ; Benzene ; trans-dichloroethylene ; Isopropanol
48. Toluene	Toluene
55. 2-(2-butoxyethoxy)ethanol (DEGBE)	2-(2-butoxyethoxy)ethanol; diethylene glycol monobutyl ether
72. The substances listed in column 1 of the Table in Appendix 12	Benzene

Contains substance on the REACH candidate list in concentration $\geq 0.1\%$ or with a lower specific limit: Phenolphthalein (EC 201-004-7, CAS 77-09-8)

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Germany

VwVwS Annex reference

: WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)

Employment restrictions

: Observe restrictions according Act on the Protection of Working Mothers (MuSchG)
Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV

: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen

: Phenolphthalein, Benzene are listed

SZW-lijst van mutagene stoffen

: Benzene is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding

: None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid

: Phenolphthalein is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling

: Toluene, Xylenes are listed

Denmark

Danish National Regulations

: Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

	CAS (Chemical Abstracts Service) number
	GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
	OSHA: Occupational Safety & Health Administration
	TSCA: Toxic Substances Control Act

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

	ATE: Acute Toxicity Estimate
	CLP: Classification, Labelling, Packaging.
	EC50: Environmental Concentration associated with a response by 50% of the test population.
	European List of Waste (LoW) code
	LD50: Lethal Dose for 50% of the test population
	STEL: Short Term Exposure Limits
	TWA: Time Weighted Average

Data sources : European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>. Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Acute Tox. 4 (Inhalation:dust,mist)	H332
Eye Irrit. 2	H319
Muta. 2	H341
Carc. 1B	H350
Repr. 2	H361
Aquatic Chronic 3	H412

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Carc. 1B	Carcinogenicity, Category 1B
Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 1B	Germ cell mutagenicity, Category 1B
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.

Tempilaq® Advanced 450 °F (232 °C), 500 °F (260 °C)

Safety Data Sheet

according to Regulation (EU) 2015/830

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H340	May cause genetic defects.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Eye Irrit. 2	H319	Calculation method
Muta. 2	H341	Calculation method
Carc. 1B	H350	Calculation method
Repr. 2	H361	Calculation method
Aquatic Chronic 3	H412	Calculation method

SDS Prepared by: The Redstone Group

110 Polaris Pkwy
Suite 200
Westerville, OH USA 43082
P: +1 (614) 923-7472
www.redstonegrp.com

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.